

SQL_TEX

v2.1

Oscar van Eijk

Jan 21, 2022

Contents

1	Introduction	2
1.1	Known limitations	2
2	Installing SQL_TEX	2
2.1	Requirements	2
2.2	Installation	3
2.2.1	Linux	3
2.2.2	Windows	4
2.2.3	OpenVMS	4
2.3	Configuration	4
2.4	Create replace files	6
2.4.1	Regular expressions	7
3	Write your SQL_TEX file	8
3.1	SQL statements	9
3.2	Opening the database	10
3.2.1	Prompt for password and/or username	10
3.3	Reading a single field	10
3.3.1	Define variables	10
3.4	Reading rows of data	11
3.4.1	Output rows on separate lines	12
3.4.2	Store data in an array	12
3.5	Loop context	12
3.6	Output multiple documents	13
3.7	Update database records	14
4	Process your SQL_TEX file	14
4.1	Parameters	14
4.2	Command line options	14

5	SQL_TE_X errors and warnings	16
6	Copyright and disclaimer	18
7	History	18

1 Introduction

SQL_TE_X is a preprocessor to enable the use of SQL statements in L^AT_EX. It is a perl script that reads an input file containing the SQL commands, and writes a L^AT_EX file that can be processed with your L^AT_EX package.

The SQL commands will be replaced by their values. It's possible to select a single field for substitution substitution in your L^AT_EX document, or to be used as input in another SQL command.

When an SQL command returns multiple fields and or rows, the values can only be used for substitution in the document.

1.1 Known limitations

- The L^AT_EX `\includeonly` directive is ignored; all documents included with `\include` will be parsed and written to the output file.
- Currently, only 9 command- line parameters (1-9), and 10 variables (0-9) can be used in SQL statements.
- Replace files can hold only 1,000 items.
- In multidocument mode, only one parameter can be retrieved.

2 Installing SQL_TE_X

Before installing SQL_TE_X, you need to have it. The latest version can always be found at <https://github.com/oveas/sqltex>. The download consists of this documentation, an installation script for Unix (`install`), and the Perl script SQL_TE_X, and a replace- file (`SQLTEX.r.dat`) for manual installation on non- unix platforms¹.

2.1 Requirements

SQL_TE_X requires the following software:

- Perl v5.10 or higher (<http://perl.org/>)
- Perl-DBI (<http://dbi.perl.org/>)

¹on Unix, this file will be generated by the install script

- The DBI driver for your database
(see: <http://search.cpan.org/search?query=DBD%3A%3A&mode=module>)
- Getopt::Long (<https://metacpan.org/pod/Getopt::Long>)
- Term::ReadKey (<https://metacpan.org/pod/Term::ReadKey>)

2.2 Installation

To install SQL_T_E_X, unpack the archive in a location of your choice and follow the steps below.

2.2.1 Linux

Go to the top directory where the archive was unpacked (`cd sqltex-2.1`) and execute the following commands:

```
$ ./configure [options]
$ make
$ [sudo] make install
```

In the last command, `sudo` is only required if the install destination (`PREFIX`, see below) is outside the own user environment.

For `configure`, the following options are user by SQL_T_E_X (type `./configure --help` for a full list):

`--prefix=PREFIX` install architecture-independent files in PREFIX. Default is `/usr/local`.

`--exec-prefix=EPREFIX` install architecture-dependent files in EPREFIX. Default is PREFIX.

The directives above are used by the ones below:

`--bindir=DIR` Location of the SQL_T_E_X script. Default is EPREFIX/bin

`--sysconfdir=DIR` Location of the Configuration- and replacefiles. Default is PREFIX/etc

`--datarootdir=DIR` Data root, used by the directives below. Default is PREFIX/share

`--mandir=DIR` Location of the SQL_T_E_X manpage. Default is DATAROOTDIR/man

`--docdir=DIR` Documentation root, used by `pdfdir` below. Default is DATAROOTDIR/doc/sqltex

`--pdfdir=DIR` Location of SQL_T_E_X.pdf. Default is DOCDIR

After installation, the archive and `unpack-` directory can be removed.

2.2.2 Windows

This distribution contains an .EXE file that was generated using PAR::Packer (<https://metacpan.org/pod/PAR::Packer>) with Strawberry Perl (<https://strawberryperl.com/>).

The files `sqltex-2.1\SQLTeX.EXE`, `sqltex-2.1\src\SQLTeX.cfg` and `sqltex-2.1\src\SQLTeX.r.dat` must be placed manually in the directory of your choice, all in the same directory.

2.2.3 OpenVMS

On OPENVMS the files must be copied manually to the destination. All files must reside in the same location:

```
$ COPY [.SQLTEX-2.1.SRC]SQLTEX.PL SYS$SYSTEM:
$ COPY [.SQLTEX-2.1.SRC]SQLTEX.CFG SYS$SYSTEM:
$ COPY [.SQLTEX-2.1.SRC]SQLTEX_R.DAT SYS$SYSTEM:
$ SET FILE/PROTECTION=(W:RE) SYS$SYSTEM:SQLTEX.PL
```

Next, define the command `SQLTEX` by setting a symbol, either in the `LOGIN.COM` for all users who need to execute this script, or in some group- or system wide login procedure, with the command:

```
$ SQLTEX := "PERL SYS$SYSTEM:SQLTEX.PL"
```

2.3 Configuration

The configuration file `SQLTeX.cfg` is located in `/etc` (linux) or the same location where `SQLTeX` is installed (all other operating systems). Multiple configuration files can be created, the command line option `--configfile` can be used to select the requested configuration.

Note: If a 1.x version of `SQLTeX` is installed on your system, make sure you save the configuration section, which was inline in older versions.

Some values can be overwritten using command line options (see section 4.2). When the command line options are omitted, the values from the requested configuration file will be used.

dbdriver Database driver. The default is `mysql`. Other supported databases are `Pg`, `Sybase`, `Oracle`, `Ingres`, `mSQL` and `PostgreSQL`, but also others might work without modification.

If your database driver is not support, look for the function `db_connect` to add support (and please notify me :)

texex The default file extension for `LaTeX` file. When `SQLTeX` is called, the first parameter should be the name of the input file. If this filename has no extension, `SQLTeX` looks for one with the default extension.

stx An output file can be given explicitly using the ‘`--output`’ option. When omitted, `SQLTEX` composes an output file name using this string.

E.g, if your input file is called `db-doc.tex`, `SQLTEX` will produce an outfile with the name `db-docstx.tex`.

def_out_is_in By default, when no output file is specified or an output file without (relative) path is given, the output file will be generated in the current directory.

This behaviour changed in version 2.1. In older version, the location of the output file always was the same as the input file location. To revert to the old behaviour, set `def_out_is_in` to ‘1’².

rfile_comment The comment-sign used in replace files. If this is empty, comments are not allowed in the replace files.

rfile_regexploc This must be part of the value `rfile_regexp` below.

rfile_regexp Explains how a regular expression is identified in the replace files (see section 2.4.1).

cmd_prefix `SQLTEX` looks for SQL commands in the input file. Commands are specified in the same way all `LATEX` commands are specified: a backslash (`\`) followed by the name of the command.

All `SQLTEX` commands start with the same string. By default, this is the string `sql`. When user commands are defined that start with the same string, this can be changed here to prevent conflicts.

sql_open This string is appended to the `cmd_prefix` to get the complete `SQLTEX` command for opening a database.

With the default configuration this command is “`\sqldb`”.

sql_field This string is appended to the `cmd_prefix` to get the complete `SQLTEX` command to read a single field from the database.

With the default configuration this command is “`\sqlfield`”.

sql_row This string is appended to the `cmd_prefix` to get the complete `SQLTEX` command to read one or more rows from the database.

With the default configuration this command is “`\sqlrow`”.

sql_params This string is appended to the `cmd_prefix` to get the complete `SQLTEX` command to retrieve a list of fields that will be used as parameters (`$PAR1`, see section 4.1) in the multidocument environment (see section 3.6).

With the default configuration this command is “`\sqlparams`”.

² Note the pre-v2.1 implementation also contained a bug: if the output file name contained an absolute or relative path, this path was always taken as relative from the input file location. In the new implementation, `def_out_is_in` is ignored if the output file name contains a path.

sql_update This string is appended to the `cmd_prefix` to get the complete SQL_{TEX} command to update one or more rows in the database.

With the default configuration this command is “`\sqlupdate`”.

sql_start This string is appended to the `cmd_prefix` to get the complete SQL_{TEX} command start a section that will be repeated for every row from an array (see section 3.5).

With the default configuration this command is “`\sqlstart`”.

sql_use This string is appended to the `cmd_prefix` to get the complete SQL_{TEX} command use a named variable from the array that is currently being processed in a loop context (see section 3.5).

With the default configuration this command is “`\sqluse`”.

sql_end This string is appended to the `cmd_prefix` to get the complete SQL_{TEX} command to end a loop context (see section 3.5).

With the default configuration this command is “`\sqlend`”.

repl_step Replacing strings (see section 2.4 below) is done two steps, to prevent values from being replaced twice. This setting—followed by a three-digit integer - “000” to “999”—is used in the first step and replaces values from the first column. In the second step, values from the second column replace the temporary value.

If the first column in the replace file contains a character sequence that occurs in this temporary value, or if query results might contain the full string followed by three digits, this value might need to be changed in something unique.

alt_cmd_prefix In loop context, this setting is used internally to differentiate between sql statements to process immediately and sql statements on stack.

Normally, this setting should never change, but if the value for `cmd_prefix` has been changed and a conflict is found, the message “**Configuration item 'alt_cmd_prefix' cannot start with <conflicting value>**” indicates this setting should change as well.

2.4 Create replace files

Replace files can be used to substitute values in the output of your SQL commands with a different value. This is especially useful when the database contains characters that are special characters in L^AT_EX, like the percent sign (`'%`), underscore (`'_'`) etc.

When SQL_{TEX} is installed, it comes with a standard file—`SQLTeX_r.dat`—which is located in `/etc` (linux) or the same location where SQL_{TEX} is installed (all other operating systems), with the following replacements:

```

$      \$
-      \_
%      \%
&      \&
<      \texttt{<}
>      \texttt{>}
{      \{
}      \}
#      \#
~      \~{}
\      \ensuremath{\backslash}

```

These are all single character replacements, but you can add your own replacements that consist of a single character or a character sequence (or even regular expressions, see section 2.4.1).

To do so, enter a new line with the character(string) that should be replaced, followed by one or more TAB-character(s) (*not* blanks!) and the character(string) it should be replaced with.

If the first non-blank character is a semicolon (;), the line is considered a comment line³. Blank lines are ignored.

The contents of the file are case sensitive, so if you add the line:

```
LaTeX      \LaTeX\
```

the word “LaTeX” will be changed, but “latex” is untouched.

Different replace files can be created. To select a different replace file for a certain SQLTeX source, use the commandline option ‘--replacementfile *filename*’. To disable the use of replace files, use ‘no-replacementfile’.

2.4.1 Regular expressions

The replace file can include regular expressions, which are recognized by a pattern given in the configuration setting `rfile_regexp`. A part of the pattern, configurable as `rfile_regexploc`, will be the actual regular expression.

By default, `rfile_regexploc` is “...” and `rfile_regexp` is “re(...)”. If the sequence of three dots can appear anywhere else in the replace file, `rfile_regexploc` can be changed to any other sequence of characters, e.g. “regexpHere”.

This also requires `rfile_regexp` to be changed. Its new value has to be “re(regexpHere)”

Both in the default configuration and with the modification example given above, the key for regular expressions is `re(<regular expression>)`, e.g.:

```
re(<p\.*?>) \paragraph*{}
```

³ in the default configuration. See the description for `rfile_comment` in section 2.3 to change of disable comment lines.

will replace all HTML `<p>` variants (`<p style='font-size: normal'>`, `<p align='center'>` etc)

An example replacement file using regular expressions to handle HTML codes could look like this:

```
&amp;          \&
<strong>      \textbf{
</strong>    }
<em>         \textit{
</em>       }
re(<br.*?/?>) \\
re(<p.*?>)   \paragraph*{
</p>       }
<sup>        $^{
</sup>      }$
re(<span.*?>) \textsl{
</span>    }
re(<h1.*?>)  \section{
re(<h2.*?>)  \subsection{
re(<h3.*?>)  \subsubsection{
re(</h\d>)   }
```

3 Write your SQL_{TEX} file

For SQL_{TEX}, you write your L^AT_EX document just as you're used to. SQL_{TEX} provides you with some extra commands that you can include in your file.

The basic format⁴ of an SQL_{TEX} command is:

```
\sqlcmd [options]{SQL statement}
```

All SQL_{TEX} commands can be specified anywhere in a line, and can span multiple lines. When SQL_{TEX} executes, the commands are read, executed, and their results—if they return any—are written to the output:

<i>Input file:</i>	<i>Output file:</i>
<code>\documentclass[article]</code>	<code>\documentclass[article]</code>
<code>\pagestyle{empty}</code>	<code>\pagestyle{empty}</code>
<code>\sqldb[oscar]{mydb}</code>	
<code>\begin{document}</code>	<code>\begin{document}</code>

Above you see the SQL_{TEX} command `\sqldb` was removed. Only the command was removed, not the *newline* character at the end of the line, so an empty line will be printed instead. The example below shows the output if an SQL_{TEX} command was found on a line with other L^AT_EX directives:

⁴in this document, in all examples will be asumed the default values in the configuration section as described in section 2.3, have not been changed

<i>Input file:</i>	<i>Output file:</i>
<code>\documentclass[article]</code>	<code>\documentclass[article]</code>
<code>\pagestyle{empty}\sqldb[oscar]{mydb}</code>	<code>\pagestyle{empty}</code>
<code>\begin{document}</code>	<code>\begin{document}</code>

In these examples the `SQLTEX` commands did not return a value. When commands actually read from the database, the returned value is written instead:

<i>Input file:</i>	<i>Output file:</i>
This invoice has <code>\sqlfield{SELECT</code>	This invoice has 3 lines
<code>COUNT(*) FROM INVOICE.LINE</code>	
<code>WHERE INVOICE_NR = 20190062} lines.</code>	

3.1 SQL statements

This document assumes the reader is familiar with SQL commands. This section only tells something about implementing them in `SQLTEX` files, especially with the use of command parameters and variables. Details about the `SQLTEX` commands will be described in the next sections.

Let's look at a simple example. Suppose we want to retrieve all header information from the database for a specific invoice. The SQL statement could look something like this:

```
SELECT * FROM INVOICE WHERE NR = 20190062;
```

To implement this statement in an `SQLTEX` file, the `\sqlrow` command should be used (see section 3.4):

First, it is important to know that SQL statements should *not* contain the ending semicolon (;) in any of the `SQLTEX` commands. The command in `SQLTEX` would be:

```
\sqlrow{SELECT * FROM INVOICE WHERE NR = 20190062}
```

Next, `SQLTEX` would be useless if you have to change your input file every time you want to generate the same document for another invoice.

Therefore, you parameters or variables can be used in your SQL statement. Parameters are given at the command line (see section 4.1), variables can be defined using the `\sqlfield` command as described in section 3.3.1.

Given the example above, the invoice number can be passed as a parameter by rewriting the command as:

```
\sqlrow{SELECT * FROM INVOICE WHERE NR = $PAR1}
```

or as a variable with the code line:

```
\sqlrow{SELECT * FROM INVOICE WHERE NR = $VAR0}
```

Note you have to know what datatype is expected by your database. In the example here the datatype is `INTEGER`. If the field "INVOICE_NR" contains a `VARCHAR` type, the `$PARAMETER` or `$VARIABLE` should be enclosed by quotes:

```
\sqlrow{SELECT * FROM INVOICE WHERE NR = '$PAR1'}
```

3.2 Opening the database

Before any information can be read from a database, this database should be opened. This is done with the `\sqldb` command. `\sqldb` requires the name of the database. Optionally, a username, password and remote database host can be given.

The format of the command is:

```
\sqldb[user=username,passwd=password,host=host]{database}
```

The command can be used anywhere in your input file, but should occur before the first command that tries to read data from the database.

If the keywords `user`, `passwd` and `host` are omitted, `SQLTEX` assumes the options are given in this order:

```
\sqldb[username,password,host]{database}
```

Default host is localhost, the default user is the current user.

3.2.1 Prompt for password and/or username

If a password is omitted, `SQLTEX` will try connect to the database without a password, unless the commandline option `--password` is given (see section 4.2).

Forcing a user to enter a database password when `SQLTEX` runs can be achieved by specifying `?` as password:

```
\sqldb[user=dbUser,passwd=?]{database}
```

When different database users should be able to use the same `SQLTEX` file, the username can also be a questionmark, forcing `SQLTEX` to prompt for a username:

```
\sqldb[user=?,passwd=?]{database}
```

3.3 Reading a single field

When a single field of information is to be read from the database, the command `\sqlfield` is used. By default, the command in the inputfile is replaced by its result in the outputfile.

The SQL command is enclosed by curly braces. Square brackets can optionally be used to enter some extra options. Currently, the only supported option is `setvar` (see section 3.3.1).

The full syntax of the `\sqlfield` command is:

```
\sqlfield[options]{SELECT fieldname FROM tablename WHERE your where-clause}
```

By default, the `SQLTEX` command is replaced with the value returned by the SQL query. This behaviour can be changed with options.

3.3.1 Define variables

The `\sqlfield` can also be used to set a variable. The value returned by the SQL query is not displayed in this case. Instead, a variable is created which can be used in any other SQL query later in the document (see also section 3.1).

Therefore, the option `[setvar=n]` is used, where *n* is an integer between 0 and 9.

Suppose you have an invoice in L^AT_EX. SQL_TE_X is executed to retrieve the invoice header information from the database for a specific customer. Next, the invoice lines are read from the database.

You could pass the invoice number as a parameter to SQL_TE_X for use in your queries, but that could change every month. It is easier to :

- pass the customer number as a parameter,
- retrieve the current date (assuming that is the invoice date as stored in the database by another program), and store it in a variable:

```
\sqlfield[setvar=0]{SELECT DATE_FORMAT(NOW(), "%Y-%m-%d")}
```

This creates a variable that can be used as \$VAR0,
- retrieve the invoice number using the customer number (a command line parameter, see also section 4.1) and the variable containing the invoice date. Store this invoice number in \$VAR1:

```
\sqlfield[setvar=1]{SELECT NR FROM INVOICES  
WHERE CUST_NR = '$PAR1' AND INVOICE_DATE = '$VAR0'}
```
- use \$VAR1 to retrieve all invoice information.

The SQL queries used here do not display any output in your L^AT_EX document.

3.4 Reading rows of data

When an SQL query returns more information than one single field, the SQL_TE_X command `\sqlrow` should be used. As with the `\sqlfield`, command, SQL_TE_X replaces the command with the values it returns, but `\sqlrow` accepts different options for formatting the output.

By default, fields are separated by a comma and a blank (‘, ’), and rows by a newline character (‘\’). To change this, the options “`fldsep`” and “`rowsep`” can be used.

e.g. In a `tabular` environment the fields should be separated by an ampersand (&), perhaps a line should separate the rows of information. (`\ \hline`).

To do this, the options can be used with `\sqlrow` as shown here:

```
\sqlrow[fldsep=&,rowsep=\ \hline]{SELECT I.NR, A.NR, A.PRICE, I.AMOUNT,  
(A.PRICE * I.AMOUNT) FROM ARTICLE A, INVOICE.LINE I WHERE I.NR = $VAR1  
AND I.ARTICLE_NR = A.NR}
```

This will produce an output like:

```
1 & 9712 & 12 & 1 & 12 \ \hline 2 & 4768 & 9.75 & 3 & 29.25 \ \hline  
3 & 4363 & 1.95 & 10 & 19.5 \ \hline 4 & 8375 & 12.5 & 2 & 25 \ \hline
```

3.4.1 Output rows on separate lines

Some L^AT_EX packages require input on a separate line. If this output is to be read from a database, this can be set with the `rowsep` option using the fixed text “NEWLINE”.

Changing the example from section 3.4 above to:

```
\sqlrow[fldsep=&,rowsep=\\ \hline NEWLINE]{SELECT I.NR, A.NR, A.PRICE,
I.AMOUNT, (A.PRICE * I.AMOUNT) FROM ARTICLE A, INVOICE_LINE I WHERE
I.NR = $VAR1 AND I.ARTICLE_NR = A.NR}
```

would produce the following result:

```
1 & 9712 & 12 & 1 & 12 \\ \hline
2 & 4768 & 9.75 & 3 & 29.25 \\ \hline
3 & 4363 & 1.95 & 10 & 19.5 \\ \hline
4 & 8375 & 12.5 & 2 & 25 \\ \hline
```

3.4.2 Store data in an array

The `\sqlrow` command can also be used to store the data in an array. The value returned by the SQL query is not displayed in this case. Instead, an array is created which can be used later in the document in a loop context (see section 3.5).

Therefore, the option `[setarr=n]` is used, where *n* is an integer between 0 and 9.

3.5 Loop context

In a loop context, an array is filled with data from the database using `\sqlrow`. Later in the document, the data can be used in a textblock that will be written to the outputfile once for every record retrieved.

The textblock is between the `\sqlstart{n}` and `\sqlend{n}` commands, where *n* is the sequence number of the array to use⁵.

Multiple textblocks can occur in the document, but they can *not* be nested!

In the example below, data for unpaid invoices is stored in an array identified with sequence number 0:

```
\sqlrow[setarr=0]{SELECT I.NR AS nr
, I.DUE_DATE AS date
, I.TOTAL AS amount
, C.NAME AS customer
FROM INVOICE I
LEFT OUTER JOIN CUSTOMER C
ON C.NR = I.CUST_NR
WHERE I.PAY_DATE IS NULL}
```

⁵ in `\sqlend`, the sequence number is ignored, but required by syntax.

To use this data, a textblock must start with: `\sqlstart{0}`
 Between this command and the first occurrence of `\sqlend{}`, an unlimited amount⁶ of L^AT_EX text can be written. Within this text, every occurrence of `\sqluse{<field name>}` will be replaced with the matching field from the current row, e.g.:

```
\sqlstart{0}
\begin{flushright}
Regarding: invoicenumber \sqluse{nr}
\end{flushright}
```

Dear `\sqluse{customer}`,

On `\today`, the invoice with number `\sqluse{nr}`, payable before `\sqluse{date}`, was not yet received by us.

We kindly request you to pay the amount of `\texteuro\sqluse{amount}` as soon as possible.

```
\newpage
\sqlend{}
```

3.6 Output multiple documents

A single input file can be created to generate more output files using the `--multidoc-numbered` or `--multidoc-named` commandline option.

The input document must contain the command `\sqlsetparams` without any options. The query that follows can return an unlimited number of rows all containing exactly 1 field:

```
\sqlsetparams{SELECT NR FROM INVOICES WHERE PAY_DATE = NULL}
```

By processing this command, SQL_TE_X builds a list with all values retrieved and processes the input file again for each value.

In those runs, the queries are executed as described in the previous sections, using the value as a parameter:

```
\sqlrow{SELECT * FROM INVOICES WHERE NR = $PAR1}
```

The options `--multidoc-numbered` or `--multidoc-named` cannot be used together.

Without these options, a parameter can be given and a single output document will be created, ignoring the `\sqlsetparams` command.

With the `--multidoc-numbered` option, output filenames will be numbered *filename_1.tex* to *filename_n.tex*.

With the `--multidoc-named` option, output filenames will be numbered *filename_parameter.tex*, where *parameter* is the value taken from the database (the incoie number nr in

⁶ limited by your computer's memory only

the example above).

Note the parameter will not be formatted to be filename-friendly!

3.7 Update database records

Since version 1.5, SQL_{TEX} supports database updates as well:

```
\sqlupdate{UPDATE INVOICE SET REMINDERS = REMINDERS + 1, LAST_REMINDER  
= NOW() WHERE NR = $VAR1}
```

This command accepts no options.

By default, the update statements will be ignored. The actually process them, the commandline options `--updates` must be given!

4 Process your SQL_{TEX} file

To process your SQL_{TEX} file and create a L^AT_EX file with all information read from the database, call SQL_{TEX} with the parameter(s) and (optional) commandline options as described here.

4.1 Parameters

SQL_{TEX} accepts more than one parameter. The first parameter is required; this should be the input file, pointing to your L^AT_EX document containing the SQL_{TEX} commands.

By default, SQL_{TEX} looks for a file with extension `.tex`.

All other parameters are used by the queries, if required. If an SQL query contains the string `$PAR n` ⁷, it is replaced by that parameter (see also section 3.1).

4.2 Command line options

SQL_{TEX} accepts the following command- line options:

`--configfile file, -c file` SQL_{TEX} configuration file. Default is `SQLTeX.cfg` in the same location where SQL_{TEX} is installed.

`--file-extension string, -E string` replace input file extension in outfile: `input.tex` will be `input.string`.

For further notes, see option `--filename-extend` below.

`--filename-extend string, -e string` add *string* to the output filename: `input.tex` will be `inputstring.tex`. This overwrites the configuration

⁷where n is a number between 1 and 9. Note parameter '0' cannot be used, since that contains the filename!

setting `stx`.

In *string*, the values between curly braces `{}` will be substituted:

P*n* parameter *n*

M current monthname (*Mon*)

W current weekday (*Wdy*)

D current date (*yyyymmdd*)

DT current date and time (*yyyymmddhhmmss*)

T current time (*hhmmss*)

e.g., the command

```
SQLTeX --filename-extend _{P1}_{W} my_file code
will read 'my_file.tex' and write 'myfile_code_Tue.tex'.
```

The same command, but with option `---file-extension` would create the outputfile `my_file._code.Tue`

The options `--file-extension` and `--filename-extend` cannot be used together or with `--output`.

`--force`, `-f` force overwrite of existing files. By default, `SQLTeX` exits with a warning message if the outputfile already exists.

`--help`, `-h` print this help message and exit.

`--multidoc-numbered`, `-m` Multidocument mode; create one document for each parameter that is retrieved from the database in the input document (see section 3.6). This option cannot be used with `--output`.

`--multidoc-named`, `-M` Same as `--multidoc-numbered`, but with the parameter in the filename instead of a serial number (see section 3.6).

`--null-allowed`, `-N` NULL return values allowed. By default `SQLTeX` exits if a query returns an empty set.

`--output file`, `-o file` specify an output file. Cannot be used with `--file-extension`, `--filename-extend` or the `--multidoc` options.

`--prefix prefix`, `-p prefix` prefix used in the `SQLTeX` file. Default is `sql` (see also section 2.3 on page 5. This overwrites the configuration setting `cmd_prefix`.

`--password [password]`, `-P [password]` database password. The value is optional; if omitted, `SQLTeX` will prompt for a password. This overwrites the password in the input file.

`--quiet`, `-q` run in quiet mode.

`--replacementfile replace, -r replace` Specify a file that contains the replace characters (see section 2.4).
 Default is `SQLTeX_r.dat` in the same location where `SQLTeX` is installed.

`--no-replacementfile, -R` Do not use a replace file. `--no-replacementfile` and `--replacementfile file` are handled in the same order as they appear on the command line, overwriting each other.
 For backwards compatibility, `-rn` is also still supported.

`--use-local-config, -l` Use the current installation directory as default location for the config- and replacement files in stead of `/etc`⁸.

`--sqlserver server, -s server` SQL server to connect to. Default is `localhost`.

`--updates, -u` if the input file contains updates, process them.

`--username user, -U user` database username. This overwrites the username in the input file.

`--version, -V` print version number and exit.

5 SQLTeX errors and warnings

no input file specified

SQLTeX was called without any parameters.

Action: Specify at least one parameter at the commandline. This parameter should be the name of your input file.

File *input filename* does not exist

The input file does not exist.

Action: Make sure the first parameter points to the input file.

outputfile *output filename* already exists

The outputfile cannot be created because it already exists.

Action: Specify another output filename with command line option `-e`, `-E` or `-o`, or force an overwrite with option `-f` (see also section 4.2).

no database opened at line *line nr*

A query starts at line *line nr*, but at that point no database was opened yet.

Action: Add an `\sqldb` command prior to the first query statement.

insufficient parameters to substitute variable on line *line nr*

The query starting at line *line nr* uses a parameter in a WHERE- clause with `$PARn`, where *n* is a number bigger than the number of parameters passed to SQLTeX.

Action: Specify all required parameters at the command line.

⁸ linux only

trying to substitute with non existing on line *line nr*

The query starting at line *line nr* requires a variable $\$VARn$ in its WHERE- clause, where *n* points to a variable that has not (yet) been set.

Action: Change the number or set the variable prior to this statement.

trying to overwrite an existing variable on line *line nr*

At line *line nr*, a `\sqlfield` query tries to set a variable *n* using the option `[setvar=n]`, but $\$VARn$ already exists at that point.

Action: Change the number.

no result set found on line *line nr*

The query starting at line *line nr* returned a NULL value. If the option `-N` was specified at the commandline, this is just a warning message. Otherwise, `SQLTEX` exits.

Action: None.

result set too big on line *line nr*

The query starting at line *line nr*, called with `\sqlfield` returned more than one field.

Action: Change your query or use `\sqlrow` instead.

no parameters for multidocument found on line *line nr*

`SQLTEX` is executed in multidocument mode, but the statement on line *line nr* did not provide any parameters for the documents.

Action: Check your query.

too many fields returned in multidocument mode on *line nr*

In multidocument mode, the list of parameters retrieved on line *line nr* returned more than one field per row.

Action: Check your query.

start using a non-existing array on line *line nr*

An `\sqlstart` command occurs, but refers to a non-existing array.

Action: Check the sequence number of the array filled with `\sqlrow[setarr=n]` and retrieved with `\sqlstart{n}` in your input file.

`\sqluse` command encountered outside loop context on line *line nr*

Data from array is used, but the current input file position is not in the context where this data is available.

Action: Check the presence and positions of the `\sqlstart` and `\sqlend` commands in your input file.

unrecognized command on line *line nr*

At line *line nr*, a command was found that starts with “`\sql`”, but this command was not recognized by `SQLTEX`.

Action: Check for typos. If the command is a user- defined command, it will

conflict with default SQL_TE_X commands. Change the SQL_TE_X command prefix (see section 2.3).

no sql statements found in *input filename*

SQL_TE_X did not find any valid SQL_TE_X commands.

Action: Check your input file.

6 Copyright and disclaimer

The SQL_TE_X project is available from GitHub: <https://github.com/oveas/sqltex>

For bugs, questions and comments, please use the issue tracker available at <https://github.com/oveas/sqltex/issues>

Copyright© 2001-2022 - Oscar van Eijk, Oveas Functionality Provider

This software is subject to the terms of the LaTeX Project Public License; see <http://www.ctan.org/tex-archive/help/Catalogue/licenses.lppl.html>.

7 History

v2.1 released: Jan 21, 2022

- Fix bug #2 (<https://github.com/oveas/sqltex/issues/2>): standard path management for output files.
See config item `def_out_is_in` in section 2.3 to revert to pre v2.1 behaviour.
- Fix: help was not displayed on Windows
- Implemented '?' as password in `dbopen`
- Implemented '?' as username in `dbopen`
- Implemented long options
- Allow overwriting variables in multidocument mode
- Added simple automated regression tests
- Added a man page for linux users
- Rewrote the installation procedure, now using `autotools` on linux.
- On linux, change the default installation directory to `/usr/bin` and store the configuration- and replacement files in `/etc`.
- Added option `--use-local-config`.

v2.0 released: Jan 12, 2016

- Fix: Oracle support using ORASID
- Fix: Ensure replacements are handled in the same order as they appear in the replacements file
- Separate configuration file(s)
- Added the options `-c` and `-M`
- Support for regular expressions in replace files
- Implemented support for the L^AT_EX `\input` and `\include` directives
- Implemented loop context
- Skip commentlines
- Project moved from local CVS to GitHub

v1.5 *released: Nov 23, 2007*

- Support for multiple databases
- Implemented database updates (`sqlupdate`)
- Implemented multiple output documents (option `-m`)

v1.4.1 *released: Feb 15, 2005*

Fix: removed leading whitespaces added to database results before replace

v1.4 *released: May 2, 2002*

Implemented replace files

v1.3 *released: Mar 16, 2001*

First public release